



Thermal Receipt Printer

XP-Q80B

- Small size and low power consumption
- Support wall hanging function
- Support prompt and error alarm function
- Support IAP online upgrade



XP-Q80B

Thermal Receipt Printer



| | | |
|------------------------|---|---------------|
| Model | XP-Q80B | |
| Printing method | Direct thermal | |
| Media width | 79.5±0.5mm / φ 80 mm | |
| Print width | 72mm | |
| Column capacity | 576 dots/line or 512 dots/line | |
| Printing speed | 230 mm/s | |
| Interface | USB / USB+Serial | Lan / USB+Lan |
| Line spacing | 3.75mm (Adjustable by commands) | |
| Character size | ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots) | |

| | | |
|----------------------------------|---|------------|
| Barcode Character | | |
| Extension character sheet | PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251) | |
| 1D Barcode | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128 | |
| 2D Barcode | / | QR CODE |
| Input buffer | 64 Kbytes | 256 Kbytes |
| NV Flash | 256 Kbytes | |

| | |
|----------------------|--|
| Power | |
| Power adaptor | Input: AC 100~240V, 50 ~ 60Hz, Output: DC 24V/2.0A |
| Printer Input | DC 24V/2.0A |
| Cash drawer | DC 24V/1A |

| | |
|---------------------------------|----------------------|
| Physical characteristics | |
| Weight | 0.8 Kg |
| Dimensions | 180*145*130mm(D*W*H) |

| | |
|-----------------------------------|--|
| Environmental Requirements | |
| Work environment | Temperature (0 ~ 45°C) humidity(10 ~ 80%) |
| Storage environment | Temperature(-10 ~ 60°C) humidity(10 ~ 90%) |

| | |
|--------------------------|------------------|
| Reliability | |
| Auto cutter | Partial |
| Cutter life | 1.5 million cuts |
| Printer head life | 150Km |

| | |
|------------------|-------------------------------------|
| Software | |
| Emulation | ESC/POS |
| Driver | Windows/JPOS/OPOS/Linux/Android/Mac |



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
 Http://www.xprintertech.com
 Email: overseas@xprinter.net

