


Thermal Mobile Label Printer

## XP-HP2



## XP-HP2

Thermal Mobile Label Printer



Model	XP-HP2
Resolving power	203DPI
Printing method	Direct thermal printing
Printing speed	20 mm / s
Maximum print width	12 mm
Chassis	The shell is ABS.
Overall dimensions	76*107.5*30mm
Weight	146g
Processor	32-bit processor
Memory	512KB Flash memory / 64KB SDRAM
Interface	TYPE-C / Bluetooth 5.0 (Dual mode) / RFID Electronic tags
Battery capacity	3.7V/1200mAh
Charging specification	5V/1A charging
User interface	2 keys (1 switch button, 1 cover button) / 1 light (1 two-color light)
Sensor	Paper detection sensor / Open cover sensor
Medium type	Continuous label paper, gap label paper (spacing 10mm)
Paper roll diameter	The diameter of the official consumable paper roll is 43mm, and the maximum support is 45mm
Medium width	13mm/14mm/15mm
Medium thickness	120-200 micron
Paper peeling	Manual paper tearing
Deviation of printout	Vertical: <1 mm / Level: <1 mm
Environmental conditions	Operating conditions: -10 ~ 55°C, humidity (non-condensation) 25 ~ 93% Storage conditions: -20 ~ 60°C, humidity (non-condensation) 10 ~ 90%
Safety	FCC, CE, CCC, Rohs
Accessories	USB cable
Reliability	Print the first 50 km
Product features	RFID intelligent tag, APP intelligent identification tag template

### Key features

- Mini and lightweight
- The wireless distance is up to 10m.
- Direct thermal, no ink, toner, or ribbons
- 2000mAh battery-capacity

### Applications



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 3895 852  
Http://www.xprintertech.com  
Email: overseas@xprinter.net

